



KC #9802 28" REAR RACE LED LIGHT BAR

Thank you for purchasing KC HiLITES products; your satisfaction is very important to us. If you have any questions regarding this product or any other KC HiLITES products, please contact us at (888) 689-5955 or visit kchilites.com.

Parts Included:

- (1) 28" Rear Race LED Bar
- (4) 1/4"-20 x 1/2" Hex Bolt
- (4) 1/4" Flat Washer
- (4) 1/4"-20 Nut

Tools Needed:

- 7/16" Wrench or Socket
- Phillips Screwdriver
- Wiring Tools



Mounting:

1. To mount this unit, remove the end caps with a Phillips screwdriver and slide the supplied 1/4" x 1/2" bolts into the channel on the back of the light bar frame, loosely install nuts and washers. Replace the end caps.
2. The unit is now ready to mount to your choice of bracketry.
Note: "L" shape mounting bracket (pr) sold separately; Item # 9800.

Wiring:

1. To power this unit, connect the Red Wire 12V (+) to the Positive post of the vehicle's battery. Connect the Black Wire (-) to the Negative post of the battery.
2. In order to achieve the desired pre-programmed functions of this LED light bar, please note the Wire Color / Function list below.

Black: (-) Ground

Red: 12V (+) Power

Blue: 12V (+) Red Brake Trigger (outer lights)

Brown: 12V (+) Single Flashing Amber Trigger

Gray: 12V (+) Red Tail Trigger (outer lights)

Green: 12V (+) Single Solid White Trigger

White: 12V (+) Single solid Blue Trigger

Yellow: 12V (+) Single Solid Amber Trigger